

Thunderbird-E3100

Mini-ITX Single Board Computer, Server Class Chipset
Intel® Core™ 2 Duo Processor

Features

Intel Core 2 Duo processor

Intel E3100 server class chipset

Max. 8 GB DDR2-400 ECC RAM

Graphics up to 1600 x 1200 pixels

VGA CRT

2 x Gigabit LAN

6 x USB 2.0

2 x RS232/RS422/RS485

6 x SATA

2 x PCI Express x4 slot

PCI Express Mini Card

ASF (Alert Standard Format)



More Features

- LiPPERT Enhanced Management Technology
- Flash BIOS
- RoHS compliant

The Thunderbird-E3100 is a high-reliability, server-class Mini-ITX board for mission critical applications. Its E3100 server class chipset handles up to eight Gigabytes of error correcting registered DDR2 RAM (ECC RAM). Together with the Intel Core 2 Duo processor, this chipset delivers maximum throughput while showing only little power consumption, typically just about 29 watts.

The Thunderbird-E3100 features an integrated Volari Z9M GPU graphics controller. Its powerful 64-bit graphics engine works with 16MB video RAM and efficiently handles 2D operations. It supports graphics modes up to 16M true color and screen resolutions up to 1600 by 1200 pixels.

The board's interfaces comprise two Gigabit LAN ports, six USB2.0 host ports and six SATA AHCI ports. There even are two serial interfaces available, which can be configured to handle either RS232, RS422, or RS485 line levels.

There are two standard PCI Express x4 slots available for system expansion. Additionally, a PCI Express Mini Card can be used to add more functionality.

The Thunderbird-E3100 comes with LiPPERT Enhanced Management Technology (LEMT) functionality. Together with its ASF Out Of Band operation features, this allows remote control and supervision.

LiPPERT is an independent design house and manufacturer that develops and builds special customer specific solutions. Please ask for a specific quotation

Thunderbird-E3100

Mini-ITX Single Board Computer, Server Class Chipset
Intel® Core™ 2 Duo Processor



Technical Data

Board Format	Mini-ITX, 170mm x 170mm (6.69" x 6.69")	Status LED	HDD, power, standby, power mode, watchdog, MiniCard, Ethernet
Processor	Intel Core 2 Duo T7500 Intel Core 2 Duo L7500	Operating temperature	0°C...+60°C (commercial, all versions) -20°C...+60°C (industrial, all versions) -40°C...+85°C (extended, optional)
Speed	T7500: 2.2 GHz U7500: 1.06 GHz	PCI Express Bus	2 PCIe x4 slots 1 PCIe x1 Mini Card
Core Logic	E3100 server class chipset ICH 9M I/O controller	RTC Backup	Battery on board
RAM (max.)	8GB DDR2 registered ECC	Power Supply	12V ±5% or ATX power supply +3.3V, +5V, +5VSB, +12V
RAM clock	400MHz	Power Consumption	<i>Maximum</i> 37 watts <i>Average</i> 29 watts <i>Idle</i> 21 watts
Graphics	Volari Z9M GPU 16MB DDR RAM	Cooling	Active
CRT	Analog VGA 1600 x 1200 pixels	MTBF	178.802 hours at 25 °C
USB	4 x USB 2.0 host external 2 x USB 2.0 host internal	BIOS	Award BIOS BIOS parameters are also saved in FEPROM
Ethernet	2 x 1000/100/10 MBit with - Intel 82574IT - 82573V with ASF	Supported OS	Windows XP, XP Embedded, Windows Server 2003, Linux. 32 and 64 bit versions are supported.
Serial	2 x RS232/RS422/RS485		
SATA	6 AHCI ports available		
Watchdog	Yes		

Ordering Information

Ordering Number	Description
t05-0010-11	CPU module with SV Intel Core 2 Duo T7500 (2.2GHz) and E3100 chipset. Includes support CD.
t05-0011-10	CPU module with SV Intel Core 2 Duo L7500 (1.6 GHz) and E3100 chipset. Processor soldered down, passively cooled. Includes support CD.

Note: t denotes the temperature range. Use 7 for commercial, 8 for industrial and 9 for extended temperature range

06/09 · Specifications subject to change without notice · ©LIPPERT Embedded Computers GmbH · Printed in Germany
All mentioned trademarks are the properties of their respective holders.