

Thunderbird/MM (Multimedia)

Mini-ITX board with Intel® Pentium® M
1.4/1.6/1.8 GHz

Features

Intel® Pentium® M processor 7xx

Digital media interfaces: DVI-I/DVO, S/PDIF

Dual channel LVDS

S-Video output

FireWire (IEEE 1394)

1 GB DDR-SDRAM


High performance 3D graphics controller

SXGA: 2048 x 1536 pixel

Fast Ethernet 100/10 BaseT

6 x USB 2.0

Passive cooling possible



More Features

- Sound I/O AC97 compatible
- Watchdog
(software configurable)
- Flash BIOS
- Battery buffered RTC
- 1 x 3.3 V PCI slot
(V2.2 compliant)
- 1 Mini-PCI slot
(V1.0 compliant)



The Thunderbird/MM is a compact, highly integrated low-power single board computer on a Mini-ITX sized board. It belongs to LiPPERT's family of Thunderbird computers, the appendix "MM" indicates its intended multi-media usage. The integrated DVI-I/DVO video interfaces and S/PDIF audio channels make it especially well suited for multimedia applications. Two FireWire ports allow fast and easy connection to cameras and other multimedia devices.

The core of the board is the Intel® Pentium® M processor 7xx running at up to 1.8 GHz, with higher speeds being possible as new processors become available. The accompanying 82855GME chipset features a high performance 3D graphics controller with Intel® Extreme Graphics-2, supporting dual independent displays. The integrated display controller comes with up to 64 MByte improved UMA VRAM and handles up to 2048 x 1536 pixels. Long distance yet interference-free display connections can be achieved using the dual channel LVDS interface.

The Thunderbird/MM comes with floppy, PS/2 keyboard and mouse, 2 x RS232C, Ultra ATA 100 EIDE and IrDA interface on-board. A Fast Ethernet port (100/10 BaseT) provides the network connectivity. Six independent USB 2.0 ports and AC-97 Sound I/O are also integrated. A mini-PCI slot is available for system expansion that can hold all types of mini-PCI modules, for instance wireless LAN interfaces. LiPPERT also offers a range of specialized Mini-PCI modules as well as adapter modules for the DVO ports. See our website for available types.

The on-board DIMM socket can hold up to 1 GB RAM.

The Thunderbird/MM with the 1.4 GHz processor works with a +5V-only supply and is available for operation in the extended temperature range from -40°C to +85°C.

Both Windows and Linux operating systems are supported.

LiPPERT is an independent design house and manufacturer that develops and builds special customer specific solutions. Please ask for a quotation.

Thunderbird/MM (Multimedia)

Mini-ITX board with Intel® Pentium® M
1.4/1.6/1.8 GHz

Board Format	Mini-ITX, 170 mm x 170 mm	Ethernet	1 x 100/10 BaseT with i82801DB
Processor	Intel® Pentium® M processor 7xx	Keyboard, Mouse	PS/2 or USB
Speed	1.4 / 1.6 / 1.8 GHz	IDE	4 independent drives Primary and Secondary ports Ultra ATA 100/66/33 Mbyte/s, PIO modes
FSB	400+ MHz	Sound I/O	6 channel AC97 2.2, 18 bit full duplex S/PDIF interface, optical
Core logic	i82855 GME i82801 DB (ICH4) Super I/O: NSC PC87364	RTC Backup	Battery on board
RAM (max.)	1024 Mbyte DDR SDRAM (PC2700) One slot available (ECC is supported)	Watchdog	Software configurable, 1s ... 255 minutes
RAM clock	200 / 266 / 333 MHz	Power Consumption (maximum)	1.4 GHz: ~19 W (with +5 V-only supply) 1.6 GHz: ~30 W 1.8 GHz: ~34 W
Graphics	Integrated i82855 graphics controller 1600 x 1200 at 85 Hz 2048 x 1536 at 75 Hz	Operating temperature	Standard: -20°C ... +60°C Extended: -40°C ... +85°C available for the 1.4 GHz version
CRT	Analog VGA (on DVI-I connector)	MTBF	> 100.000 h at 30 °C (t.b.d.)
DVI-I	up to 165 Megapixel/second	Cooling	Passive cooling possible
DVO	2 ports at 165 MHz pixel clock each	Status LED	Power, Ethernet, IDE
LVDS	Dual channel 18-Bit interface for displays	PCI Bus	1 x Standard PCI slot, 3.3V V2.2 compliant 1 x Mini-PCI slot, V1.0 compliant, type IIIA
S-Video	TV output with TV connection detection	Power Supply	ATX. A +5 V only supply can be used optionally. All necessary voltages are generated on-board.
Floppy	up to 2.88 Mbyte	BIOS	Phoenix FirstBIOS. The BIOS parameters are also saved in FEPROM
Serial	2 x RS232C with hardware handshake	Supported OS	Windows® XP, Windows® XPE, Windows® CE, Linux®
Infrared	IrDA (SIR, Consumer IR) with TTL level to connect an external infrared transmitter		
USB	6 x USB 2.0		
FireWire	2 x IEEE1394		

Ordering Information

Ordering Number	Description
805-0003-11	Mini-ITX board with socketed 1.8 GHz Pentium® M 745, max. 1GB DDR-RAM, 6xUSB 2.0, DVI-I/DVO, t-Video, IrDA, RTC, Battery, FDC, 2xIDE, 2xCOM, PS/2 keyboard and mouse, watchdog, PCI slot, miniPCI slot, Ethernet, 2xIEEE1394, LVDS, AC97 sound, S/PDIF, ATX power connector
805-0003-10	Like 805-0003-11 but with 1.6 GHz Pentium® M
805-0004-10	Like 805-0003-10 but with soldered 1.4 GHz Pentium® M 738, passive cooler and 5 volt single voltage supply

Note: t denotes the temperature range. Substitute with 8 for standard and 9 for extended temperature range

LiPPERT Embedded Computers GmbH
Hans-Thoma-Str. 11 · D-68163 Mannheim
Phone +49 621 43214-0 · Fax +49 621 43214-30
sales@lippertembedded.com
www.lippertembedded.com

LiPPERT Embedded Computers Inc.
5555 Glenridge Connector, Suite 200
Atlanta, GA 30342
Phone (404) 459 2870 · Fax (404) 459 2871
ussales@lippertembedded.com

LiPPERT
THE EMBEDDED PC COMPANY

